(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 4 November 2004 (04.11.2004)

PCT

(10) International Publication Number WO 2004/095286 A2

(51) International Patent Classification7:

G06F 12/00

(21) International Application Number:

PCT/US2004/012305

(22) International Filing Date: 21 April 2004 (21.04.2004)

(25) Filing Language:

English

(26) Publication Language:

English


(30) Priority Data:

60/464,462

22 April 2003 (22.04.2003)

- (71) Applicant (for all designated States except US): AGERE SYSTEMS INC. [US/US]; 1110 American Parkway NE, Allentown, PA 18109 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): CHIN, Chung, Kuang [US/US]; 18820 Bellgrove Circle, Saratoga, CA

- (74) Agent: MASON, Kevin, M.; Ryan, Mason & Lewis, LLP, Suite 205, 1300 Post Road, Fairfield, CT 06824 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO. CR. CU. CZ. DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).



of output ports toward which each of the packets is destined. The buffer usage count provides a mechanism for determining when a buffer is free. The buffer usage count can also indicate a number of destination ports for a packet to perform a multicasting operation. Buffers can comprise one or more groups and each of the groups can comprise a plurality of banks.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.